

COMPACT FLATWORK IRONERS S - Ø600mm

FEATURES

S models are ironers that dry and irons only, without any folding devices

- Roll dimensions: working width 2m60 and 3m30, diameter 600 mm.
- Frequency inverter.
- Feeding and ironing by Nomex quality belts.
- Panels in white painted steel.
- Polished steel roll, with finger guard.
- Touch screen control: programs can be created with speed control between 3 and 18 m/min and temperature.
- Electric, gas or steam heating.
- Powerful exhaust System.
- Automatic stop after cooling down (at 80°C).
Compressed air connexion required: pressure 6,5 bar


OPTIONS

- 1 lane automatic clamp feeder with vacuum table
- Vacuum table
- Rear exit with by-pass, standard height 850mm
- Motorized rear exit, height 870mm
- Small pieces 2 lanes back collector
- Small pieces 4 lanes back collector
- Different voltage from 400V III + N 50Hz
- Maritime packing



TECHNICAL DATA	UNIT.	S - 260/60	S - 330/60
GENERAL DATA			
Theoretical production humidity*	Kg/h	75-105*	110-140*
Ø Roll	mm	600	600
Working width	mm	2.600	3.300
Height floor-feeding	mm	1.050	1.050
Working speed	mt/min	3-10	3-10
Control type	-	Digital	Digital
Nº of programs	Nº	20	20
POWER			
Electric heating	kW	54	54
Max. electric power electric heating	kW	55,9	55,9
Gas heating (natural / LPG)	kW	63,30/67,40	80,30/86,30
Max. electric power gas heating	kW	1,9	1,9
Steam heating	kW	55	75
Max. electric power steam heating	kW	1,9	1,9
CONNECTIONS			
Ø Gas inlet	BSP	1"	1"
Ø Steam inlet (12 bar max.)	BSP	1"	1"
Ø Condensed (steam models)	BSP	1/2"	1/2"
Ø Air inlet	mm	12	12
DIMENSIONS / PACKAGING DIMENSIONS			
Net width / gross width	mm	3.670/ 3.830	4.370/4.530
Net depth / gross depth	mm	1.440/ 1.620	1.440/ 1.620
Net height / gross height	mm	2.030/ 1.960	2.030/ 1.960
Net weight / gross weight	Kg	1.800/ 2.050	2.050/ 2.350
Volume	m3	10,73/ 12,16	12,77/ 14,38
OTHERS			
No. Fume outlet	Nº	2	2
Ø Fume outlet	mm	120	120
Extraction rate	m3/h	2 x 1.000	2 x 1.000
Compressed air consumption (6,5 bar)	NI/h	5.000	5.000
Sound Level	dB	70	70

*50% residual moisture, 140gr / m2 of cotton,
100% roll utilization



- A. Compressed air inlet
- C. Condensation discharge (steam heating)
- E. Electrical connection
- F. Fumes extraction
- G. Gas inlet
- V. Steam inlet

	H	I	T	S	A	C	E	F	G	V
CY2660	1.800	3.242	186	152	Ø 12	1/2"	5 x 2,5	Ø 120	1"	1"
CY3360	1.800	3.942	186	152	Ø 12	1/2"	5 x 2,5	Ø 120	1"	1"