



### TOUCH II

7" touch screen easy to use and fully programmable, double display  
 Connection USB. Free software online for programming, telemetry, data analysis...  
 Videos on display (instructions...)  
 37 languages  
 8 dosing signals as standard



### OUTSTANDING FEATURES

Automatic positioning of drum with motor brake  
 3 water inlets  
 Wet cleaning, telemetry standard  
 G-FACTOR 375  
 Heating: electric, steam, and dual heating model (electric+steam)



### EFFICIENCY

Intelligent consumption  
 Optimal loading  
 Water Recovery tanks ready: ECOTANK  
 Low water consumption  
 High G-FACTOR: reduced residual moisture > reduced drying time



### CONNECTIVITY

IoT - Domus Connect  
 Remote technical service  
 Laundry management



### ERGONOMICS

Huge door opening making loading/unloading easier  
 Easy friendly drum opening by push button  
 Loading height: door base 800 mm



### MAINTENANCE

Electric components on the left side, mechanical components on the right side and connections on the top (protected from water and detergents)  
 Central drain as standard  
 Technical menu: statistics, alarms, autotest, data recovery for technicians and maintenance



### OTHERS

2 opposed doors. Pass-through barrier washer.  
 Ready to be connected to dosing pumps  
 Grey skinplate outer casing  
 Drum and vat in stainless steel AISI 304  
 Frequency inverter to control imbalance  
 CE approved product




### OPTIONS

- 1-door opening (single side operation)
- Auto Weight: automatic weighing sensor system on feet (Includes kit with 6 extra dosing signals)
- Relay card with 6 extra dosing signals: up to 14 signals
- Printer
- Third water inlet
- Double drain
- Titration valve
- Side drain valve
- Low steam pressure (0,5 bar)
- Detergent box with 4 compartments
- UPS device (in case of power failure)
- End of cycle light alarm
- Plinth to align loading height (door base at 850mm)
- Stainless steel AISI 304 outer casing
- Stainless steel AISI 304 sanitary frame
- Other voltages

TECHNICAL DATA	UNIT.	DHB-70 TOUCH II	
<b>DRUM</b>			
Capacity 1:9 / 1:10	Kg	78 / 70	
Volume	l	694	
Diameter	mm	800	
Depth	mm	1.380	
No of drum compartment	No	2	
Pullman partition of drum		N/A	
<b>GENERAL DETAILS</b>			
Washing / spin speed	r.p.m.	45 / 920	
G Factor	-	375	
Dynamic force	KN	5,24	
Dynamic force frequency	Hz	15,4	
Sound level	dB	<70	
Double drain	-	OPT	
Weighing system	-	OPT	
<b>DRUM</b>			
Height door bottom	mm	800	
Drum opening dimensions	mm	640 x 515 (x2)	
Vat opening dimensions	mm	1.402 x 650 (x2)	
<b>POWER</b>			
Motor	kW	7,5	
Electric heating	kW	45	
Total electric power (elec mod)	kW	52,5	
Total electric power (steam mod)	kW	7,5	
<b>CONNECTIONS</b>		<b>ELECTRIC DUAL</b>	<b>STEAM</b>
Tension 230V - I + N + T	N° x mm2 / A	-	-
Tension 230V - III + T	N° x mm2 / A	4 x 35 / 160A	4 x 2,5 / 16A
Tension 400V - III + N + T	N° x mm2 / A	5 x 16 / 80A	5 x 2,5 / 10A
steam inlet (steam mod)	Inch	3/4"	
Max. steam consumption (steam models)	Kg/h	34,2	
Water inlet	Inch	1"	
Water pressure	Kgs/cm <sup>2</sup>	3-5	
Max. water consumption*	Lit/h	720	
Drain	Inch	3"	
Drain flow	Lit/min	160	
<b>OVERALL DIMENSIONS / PACKING DIMENSIONS</b>			
Net width / Gross width	mm	2.124 / 2.310	
Net depth / Gross depth	mm	1.195 / 1.300	
Net height / Gross height	mm	1.615 / 1.720	
Net weight / Gross weight	kg	1.190 / 1.220	
Volume	m3	4,10 / 5,17	

\* N°2 Program, 100% load



01. Electrical connexion
02. Cold water inlet
03. Soft water inlet
04. Hot water inlet
05. Liquid products inlet
06. Main switch
07. Control panel
08. Emergency stop
09. Door opening
10. USB port
11. Dosing pumps connexion
12. Steam inlet
13. Exhaust
14. Cold water for detergents box

	A	B	C	A1	B1	C1	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
DHB-70	2104	1196	1612	2061	1098	1581	745	152	138	206	263	330	397	482	956	163	103	126	956	1499	1059	2210	45	125